



深圳市博索特科技有限公司

# 带阻滤波器/陷波器 2019 版



## 腔体带阻滤波器/陷波器

型号	阻带频率	通带频率	插损	驻波比	抑制	功率	接头	尺寸
	MHZ	MHZ & GHZ	dB	Typ.	dB@MHZ	W	Typ.	mm
BOST-DZA59	2320~2370MHZ	DC~2275MHZ & 2425~6000MHZ	≤2.0	≤1.5:1	≥50DB	50	N-Female	195*52*22
BOST-DZA60	2110-2170MHZ	DC~2085MHZ & 2195~5500MHZ	≤2.0	≤1.5:1	≥50DB	50	SMA-Female	185*51*22
BOST-DZA61	2400-2483MHZ	DC~2350MHZ & 2533~6000MHZ	≤2.0	≤1.5:1	≥30DB	50	SMA-Female	124*47*22
BOST-DZA62	5150-5850MHZ	DC~4900MHZ & 6100~10000MHZ	≤2.0	≤1.7:1	≥40DB	5	SMA-Female	119*30*16
BOST-DZA63	1920-1980MHZ	DC~1900MHZ & 2000~4500MHZ	≤2.0	≤1.5:1	≥35DB	50	N-Female	225*59*22
BOST-DZA64	1710-1785MHZ	DC~1685MHZ & 1810~4500MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	225*55*22
BOST-DZA65	1850-1910MHZ	DC~1825MHZ & 1940~4500MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	225*55*22
BOST-DZA66	880-915MHZ	DC~860MHZ & 935~2400MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	221*87*28
BOST-DZA67	824-846MHZ	DC~790MHZ & 866~2500MHZ	≤2.0	≤1.5:1	≥45DB	20	N-Female	248*98*28
BOST-DZA05	902-928MHZ	DC~890MHZ & 940~2700MHZ	≤2.0	≤1.5:1	≥40DB	20	SMA-Female	265*90*28
BOST-DZA68	3400-3600MHZ	DC~3360MHZ & 3640~7000MHZ	≤3.0	≤1.5:1	≥45DB	50	SMA-Female	193*42*11
BOST-DZA69	885-889MHZ	DC~875MHZ & 899~2200MHZ	≤2.0	≤1.5:1	≥40DB	20	SMA-Female	213*95*28
BOST-DZA70	930-934MHZ	DC~920MHZ & 944~2200MHZ	≤2.0	≤1.5:1	≥40DB	20	SMA-Female	213*95*28
BOST-DZA71	2570-2620MHZ	DC~2545MHZ & 2645~5500MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	165*47*22
BOST-DZA72	4800-5000MHZ	DC~4.73GHZ & 5.07~10GHZ	≤2.5	≤1.8:1	≥40DB	10	SMA-Male	141*36*16
BOST-DZA72	934-954MHZ	DC~914MHZ & 974~2500MHZ	≤1.5	≤1.5:1	≥50DB	50	N-Female	221*78.5*28
BOST-DZA73	889-909MHZ	DC~875MHZ & 923~2400MHZ	≤2.0	≤1.5:1	≥40DB	10	SMA-Female	265*90*28
BOST-DZA74	1710-1880MHZ	DC~1610MHZ & 1980~4500MHZ	≤2.0	≤1.7:1	≥50DB	20	SMA-Female	269*57*22
BOST-DZA75	2400-2500MHZ	DC~2300MHZ & 2600~6000MHZ	≤2.0	≤1.7:1	≥50DB	10	SMA	124*45*22
BOST-DZA80	2500-2570MHZ	DC~2475MHZ & 2595~5500MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	195*46*22
BOST-DZA76	1785-1805MHZ	DC~1775MHZ & 1820~4000MHZ	≤4.0	≤1.5:1	≥40DB	50	SMA-Female	225*58*22
BOST-DZA77	2515~2675MHZ	DC~2465MHZ & 2725~5200MHZ	≤2.0	≤1.7:1	≥40DB	10	SMA-Female	209*47*22
BOST-DZA78	3300-3600MHZ	DC~3220MHZ & 3680~8000MHZ	≤2.0	≤1.7:1	≥40DB	10	SMA-Female	141*40*16
BOST-DZA57	1880-1930MHZ	DC~1830MHZ & 1980~4600MHZ	≤1.5	≤1.7:1	≥40DB	50	SMA-Female	137*52*22
BOST-DZA69N	885-889MHZ	DC~875MHZ & 899~2200MHZ	≤2.0	≤1.5:1	≥40DB	20	N-Female	213*99*28
BOST-DZA70N	930-934MHZ	DC~920MHZ & 944~2200MHZ	≤2.0	≤1.5:1	≥40DB	20	N-Female	213*95*28
BOST-DZA81	2400~2483.5MHZ	1M~2.375GHZ & 2.51~6.0GHZ	≤2.0	≤1.5:1	≥50DB	20	SMA-Female	195*48*22
BOST-DZA82	704-716MHZ	DC~684MHZ & 736~2100MHZ	≤1.0	≤1.5:1	≥50DB	50	SMA-Female	229*103*28
BOST-DZA83	704-746MHZ	DC~654MHZ & 796~1500MHZ	≤2.0	≤1.7:1	≥40DB	10	SMA-Female	229*96*28
BOST-DZA84	791-821MHZ	DC~773MHZ & 839~2500MHZ	≤1.5	≤1.7:1	≥50DB	50	SMA-Female	239*95*28
BOST-DZA85	824-894MHZ	DC~774MHZ & 944~2400MHZ	≤2.0	≤1.7:1	≥50DB	20	SMA-Female	248*84*28
BOST-DZA86	824-915MHZ	DC~774MHZ & 965~2200MHZ	≤2.0	≤1.8:1	≥45DB	5	SMA-Female	248*80*28
BOST-DZA87	832-862MHZ	DC~812MHZ & 882~2400MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	221*92*28



## 腔体带阻滤波器/陷波器

型号	阻带频率	通带频率	插损	驻波比	抑制	功率	接头	尺寸
	MHZ	MHZ & GHZ	dB	Typ.	dB@MHZ	W	Typ.	mm
BOST-DZA06	864-869MHZ	DC~850MHZ & 880~2500MHZ	≤2.0	≤1.5:1	≥40DB	20	SMA-Female	213*95*28
BOST-DZA88	869-894MHZ	DC~849MHZ & 914~2600MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	221*92*28
BOST-DZA89	970-1030MHZ	DC~930MHZ & 1070~2400MHZ	≤2.0	≤1.7:1	≥50DB	10	SMA-Female	265*80*28
BOST-DZA90	1805-1880MHZ	DC~1780MHZ & 1905~5000MHZ	≤2.0	≤1.5:1	≥50DB	50	SMA-Female	225*53*22
BOST-DZA91	1920-2170MHZ	DC~1820MHZ & 2270~4500MHZ	≤2.0	≤1.7:1	≥50DB	20	SMA-Female	269*53*22
BOST-DZA92	1930-1990MHZ	DC~1900MHZ & 2020~4000MHZ	≤2.0	≤1.5:1	≥50DB	50	SMA-Female	225*55*22
BOST-DZA93	2110-2155MHZ	DC~2080MHZ & 2185~5000MHZ	≤2.0	≤1.5:1	≥45DB	20	SMA-Female	225*52*22
BOST-DZA94	2500-2690MHZ	DC~2400MHZ & 2790~5000MHZ	≤2.0	≤1.7:1	≥50DB	20	SMA-Female	209*47*22
BOST-DZA95	2620~2690MHZ	DC~2595MHZ & 2715~6000MHZ	≤2.0	≤1.5:1	≥50DB	50	SMA-Female	195*46*22
BOST-DZA96	2300-2400MHZ	DC~2275MHZ & 2425~6000MHZ	≤1.6	≤1.5:1	≥40DB	50	SMA-Female	195*48*22
BOST-DZA97	925-960MHZ	DC~907MHZ & 978-2700MHZ	≤1.5	≤1.5:1	≥50DB	50	SMA-Female	221*85*28
BOST-DZA98	623-634MHZ	DC~603MHZ & 654-13000MHZ	≤2.0	≤1.5:1	≥35DB	10	SMA-Female	248*110*28
BOST-DZA99	824-849MHZ	DC~795MHZ & 878-2000MHZ	≤2.0	≤1.5:1	≥40DB	10	SMA-Female	221*92*28
BOST-DZA100	1880-1920MHZ	DC~795MHZ & 878-2000MHZ	≤1.5	≤1.5:1	≥60DB	50	SMA-N	181*54*22
BOST-DZA101	2555-2655MHZ	DC~2400MHZ & 2800-6000MHZ	≤2.0	≤1.7:1	≥60DB	20	SMA-N	209*47*22
BOST-DZA102	2010-2025MHZ	DC~2000MHZ & 2040-6000MHZ	≤3.0	≤1.5:1	≥60DB	20	SMA-Female	245*55*22
BOST-DZA103	890-915MHZ	DC~860MHZ & 945-2400MHZ	≤2.0	≤1.5:1	≥40DB	50	SMA-Female	221*87*28
BOST-DZA104	5150-5350MHZ	DC~5100MHZ & 5400-8000MHZ	≤3.0	≤1.8:1	≥45DB	50	SMA-Female	137*31*17
BOST-DZA105	5725-5850MHZ	DC~5695MHZ & 5880-8000MHZ	≤4.0	≤1.7:1	≥45DB	50	SMA-Female	137*34*11
BOST-DZA106	5470-5850MHZ	DC~5380MHZ & 5940-8000MHZ	≤3.0	≤1.8:1	≥45DB	50	SMA-Female	137*35*11
BOST-DZA107	758-803MHZ	DC~733MHZ & 828~2190MHZ	≤1.0	≤1.7:1	≥40DB	5	SMA-Female	248*95*28
BOST-DZA108	777-787MHZ	DC~757MHZ & 807~2300MHZ	≤1.0	≤1.5:1	≥50DB	50	SMA-Female	229*96*28
BOST-DZA109	2496-2690MHZ	DC~2400MHZ & 2790-5000MHZ	≤2.0	≤1.7:1	≥50DB	20	SMA-Female	209*47*22

备注：带通滤波器，高通滤波器，低通滤波器，带阻滤波器/陷波器，除公司常规型号以外，也可以根据客户需求指标规格定制！